

ASPEE ASH799 HIGH PRESSURE KNAPSACK SPRAYER WITH HONDA ENGINE



CODE : UB001B/H



Suitable for row & ground crops like cotton, soyabean, vegetables, tea & coffee plantations, orchards & tall trees

Special Features:

- ASPEE ASH/799 is light weight & very powerful sprayer
- Economic for spraying costly pesticides
- Spray lance & spray gun supplied with sprayer
- Engine fitted with recoil starter for easy start
- Highly mobile single S.S. piston pump developing maximum pressure of 400 psi
- Light weight & compact construction
- The sprayer is equipped with auto agitation system
- Supplied with 25.0 cc engine
- Engine produces high torque for better field operation
- Diaphragm type carburetor is equipped with accelerator pump for fast, easy acceleration
- Roller bearing supported connecting rod & ball bearing supported crankshaft for greater stability
- Engine is equipped with OHC design reduces mechanical noise & Large capacity, multi-chamber exhaust system
- Efficient port configuration and large diameter valves maximize power output

ASPEE ASH799 HIGH PRESSURE KNAPSACK SPRAYER WITH HONDA ENGINE

**CODE : UB001B/H****General Description:**

ASPEE ASH/799 sprayer is an ideal partner for spraying costly pesticides. ASPEE ASH/799 sprayer is being preferred by the farmers as the most durable, efficient, & labour saving spraying equipment, which can be used for agriculture purpose. Now the ASPEE ASH/799 sprayer is available with Four stroke Honda GX-25 engine with OHC.

The sprayer is equipped with positive displacement plunger pump, 20 liter capacity chemical tank, 110 cm. long delivery hose, spray gun, spray lance, 1 set of packing gaskets. The four stroke engine reduced the operating cost approximately half time comparable two stroke engine.

| Technical Description | |
|-----------------------------------------|------------------------------------------------------------------------|
| Model | UB/001BH |
| Engine Type | Air-cooled 4-stroke OHC Petrol engine |
| Displacement | 25 cc |
| Net Power Output | 1.0 HP (.72 kw) @ 7,000 rpm |
| Net Torque | 1.0 Nm @ 5,000 rpm |
| Carburetor | Diaphragm-type (overflow return) |
| Ignition System | Transistorized magneto |
| Starting System | Recoil starter |
| Lubrication System | Crankcase pressure-driven |
| Air cleaner | Semi-dry |
| Oil tank Capacity | 80 ml |
| Fuel Tank Capacity | 500 ml |
| Chemical tank capacity | 20 ltr \pm 5 % |
| Pump type | Positive displacement reciprocating pump (single piston double acting) |
| Suction / Discharge capacity at no load | 10 to 11 ltr /min |
| Normal working pressure | 100 – 200 PSI |
| Maximum pressure | 400 PSI |
| Weight | 11.5 kg (approx) |

ASPEE®**ASPEE GROUP OF COMPANIES**

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.
Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY