

ASPEE ASM-779/M SPRAYER WITH 50 LIT. TANK WITH MARUYAMA ENGINE**CODE: UM001B/M/50T**

Suitable for row & ground crops like cotton, soyabean, vegetables, tea & coffee plantations, orchards & tall trees

General Description:

ASPEE UM001B/M/50T SPRAYER equipped with forced Air Cooled 25.6 cc petrol engine with reciprocating type metal pump. ASPEE UM001B/M/50T SPRAYER is now available with 50 lit rotomoulded plastic chemical tank With bigger filler hole, 50 meter long delivery hose, 1 spray gun, & movable trolley for easy transportation.

Special Features:

- Economic for spraying costly pesticides
- Efficient in fuel consumption 100 minutes per liter
- Develops up to 400 psi pressure
- Spray lance & spray gun supplied with sprayer
- Supplied with 25.6 cc engine
- Engine fitted with recoil starter for easy starting
- Prompt supply of spare parts & after sales services throughout the country
- Highly mobile single brass piston pump developing maximum 400 psi

ASPEE ASM-779/M SPRAYER WITH 50 LIT. TANK WITH MARUYAMA ENGINE**CODE: UM001B/M/50T**

Technical Description	
Model	UM001B/M/50T
Engine Type	2–Stroke, forced air cooled petrol engine
Displacement	25.6 cc
Net Power Output	1.0 HP (.75 kw) @ 5,000 rpm
Net Torque	1.05 Nm @ 5,000 rpm
Carburetor	Diaphragm-type (overflow return)
Ignition System	Transistorized magneto
Starting System	Recoil starter
Fuel Tank Capacity	500 ml
Pump type	Positive displacement reciprocating pump (single piston double acting)
Suction / Discharge capacity at no load	10 to 11 ltr/min
Normal working pressure	100 – 200 PSI
Maximum pressure	400 PSI
Weight	22 kg (approx)

ASPEE®**ASPEE GROUP OF COMPANIES**

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.
Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY