

ASPEE DURO TEKK UNIMOBILE HIGH PRESSURE SPRAYER



CODE: UM002B/D

Suitable for row & ground crops like cotton, soyabean, vegetables, tea & coffee plantations, orchards & tall trees

General Description:

Forced air cooled 25.6 cc petrol engine with reciprocating type metal pump & gear box mounted on frame, 15 meters delivery hose, 3 meters suction with bypass hose & coupling.

Special Features:

- Economic for spraying costly pesticides
- Efficient in fuel consumption 100 minutes per liter
- Develops up to 400 psi pressure
- Spray gun supplied with sprayer
- Supplied with 25.6 cc engine
- Engine fitted with recoil starter for easy starting
- Highly mobile single S.S. piston pump developing maximum 400 psi

ASPEE DURO TEKK UNIMOBILE HIGH PRESSURE SPRAYER



CODE: UM002B/D

Technical Description	
Model	UM002B/D
Engine type	2–Stroke, forced air cooled petrol engine
Displacement	25.6 cc
Net power output	1.0 HP (.75 kw) @ 5,000 rpm
Net torque	1.05 Nm @ 5,000 rpm
Carburetor	Ruixing Diaphragm-type tuning Carburetor
Ignition system	Transistorized magneto
Starting system	Recoil starter
Fuel tank capacity	500 ml
Pump type	Positive displacement reciprocating brass metal pump (Single piston double acting)
Suction / discharge capacity at no load	10 to 11 ltr/min
Normal working pressure	100 – 200 psi
Maximum pressure	400 psi
Weight	7.9 kg (approx)


ASPEE®

ASPEE GROUP OF COMPANIES

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064, Maharashtra, India.
 Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY