

ASPEE MARUYAMA POWER WEEDER



CODE : PW50M



It is mainly used for soil Preparation, Cultivation, Leveling off uneven fields, Inter Row Weeding etc

Special Features:

- Equipped with new Maruyama engine this high power & high torque engine make your easier
- Detachable air cleaner case & safety cover provided is provided to make the work more efficient & comfortable
- The muffler is provided with divided internal configuration to reduce the voice and makes the high power efficiently at the same time
- Full chrome-moly crankshaft
- Engine is equipped with modified recoil starter for easy starting
- Sturdy reduction type gear box is provided for power transmission
- Air cleaner is mounted with newly designed thick element for longer durability and easy maintenance and it also prevent the engine from the small dust
- Equipped with carbon steel blades for wedding purpose
- Provided with sturdy solid shaft for power transmission
- Reinforced blade (mud) guard is provided
- Engine equipped with diaphragm type carburetor
- Engine is equipped with auto centrifugal clutch

ASPEE MARUYAMA POWER WEEDER



CODE : PW50M

General Description:

ASPEE MARUYAMA POWER WEEDER is being preferred by the farmers as the most durable, efficient, & labour saving weeding equipment, which is used for agriculture purpose.

Aspee Maruyama Power Weeder is equipped with two stroke 49.9 cc petrol engine with modified recoil starter. Small straight shaft is provided for power transmission from engine to the gear box. Sturdy carbon steel blades are provided for weeding purpose.

Technical Description:	
MODEL	PW50M
Engine type	2 stroke, single cylinder, Petrol engine Forced air cooled
Engine Capacity	49.9 cc
Carburetor	Diaphragm type (Walbro)
Ignition system	TCI Solid state ignition
Max. Output Power (In Kw./HP /rpm)	1.9 Kw/2.55 HP / 7500
Max. torque	2.74 N.m. @ 5000 rpm
Fuel tank capacity	1000 ml.
Fuel consumption	60 minutes / liter
Starting system	Recoil starter (Modified)
Handle	Not adjustable
Working Depth	35 to 65 mm (1 ½" to 2 ½")
Working Width	300 mm.
Weight	15 Kg.

ASPEE®
ASPEE GROUP OF COMPANIES

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.
 Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY