



ASPEE ROTARY TILLER



CODE: RTP/GX 200

For mechanized weeding & tilling operating. Ideal for vegetable, tea garden & tobacco growing farmers. Soil preparation for seeding, cultivation, leveling of uneven field etc

General Description:

Aspee Rotary tiller is equipment with four stroke 196cc petrol engine with recoil starter, pully & belt for power transmission from the engine to the gear box. Sturdy carbon steel blades for tilling purpose, adjustable handle bars (For adjustment the height of operating handle as per operator's requirement), Rein forced chain guard, external gear lever is given for selection of several forward & backward movement. Towing hitch is provided to connect with trailer.

Special Features:

- Powerful high performance 4 stroke petrol Engine having 6.5 HP power output
- Sturdy Gear box with 2 forward gears and 1 reverse gear
- Ergonomically and anti-vibration design that reduces operators fatigue
- High carbon steel blade with protection disc and reinforced blade guard.
- Adjustable handle locking differential provided for easy direction change.
- Cost effective, labour and time saving mechanized device.
- Effectively uproots weeds and gives effective tilling.





ASPEE ROTARY TILLER



CODE: RTP/GX 200

Technical Description	
Model	RTP/GX 200
Engine Type	Single Cylinder, 4-Stroke, OHV25, Forced Air Cooling
Bore X Stroke (mm)	68 X 54
Displacement (cc)	196
Compression Ratio	8.5:1
Max. Power (kw/rpm)	4.8 (6.5) / 3600
Rated Power (kw/rpm)	4.2 (5.7) / 3600
Max. Torque (n. m)	12 / 2500
Ignition System	Transistor (Magneto)
Starting System	Recoil Start
Air Cleaner	Semi-dry, Oil Bath, Foam Filter Element
Fuel Tank Capacity (L)	3.6
Low Oil Consumption	395
(g/kw*h)	
Oil Capacity (L)	0.6



ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064, Maharashtra. India. Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com