

ASPEE V-DYUT DELUX BATTERY OPERATED SPRAYER



An efficient sprayers for tea, coffee and other field crops

General Description:

ASPEE V \sim dyut Delux battery sprayer is provided with 16 lit. capacity high density polyethylene tank. The tank is fitted with diaphragm pump. 110 cm. long delivery hose and spray lance TPHB consisting of plastic trigger cut-off, 45 cm long SS telescopic extension rod with plastic elbow and plastic nozzles, battery charger.

Special Features:

- Supplied with pressure regulator for low and high pressure
- · Pump is vertical so virtually no chance of contact with water
- Provided with stainless steel telescopic lance



ASPEE V-DYUT DELUX BATTERY OPERATED SPRAYER



CODE: VBD09

Technical Description	
Model	VBD09
Tank capacity	16 ltr
Battery	12 Volt, 7.0 AMP- Sealed lead acid
Charger	Automatic sealed lead acid 100 - 240 volt
	50/60 hz input, 12 vdc 1,000 MA output
Pump	Electric motor operated 12 Volt, 2.6 lit/min discharge @40 psi
Pump materials of construction	Polypropylene pump body, viton valves,
	santoprene diaphragm
Working pressure psi	Low pressure - 30 psi
	High pressure - 40 psi
Length of lance	100 cm
LxWxH (in mm)	335 x 140 x 470
Weight	2.5 kg (approx)



ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India. Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com