

## ASPEE BILI HTP POWER SPRAYER



**CODE: PSB16BNC**



**CODE: PSB22A1N**



Suitable for large spraying operations in orchards, coffee & tea plantations and ground crop etc.

### **General Description:**

ASPEE BILI HTP horizontal triplex power sprayer unit, developing 400 PSI (28 Bar) pressure, supplied with pulley, glycerin filled pressure gauge, by pass cum pressure regulator valve, by-pass hose & suction hose with strainer.

### **Special Features:**

- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Heavy duty industrial quality brass stamping material
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting rod

**ASPEE BILI HTP POWER SPRAYER****CODE: PSB16BNC****CODE: PSB22A1N**

Technical Description		
Model	PSB16BNC	PSB22A1N
Suction capacity (lpm)	16	20
Normal working pressure	100 - 200 PSI	100 - 200 PSI
Maximum pressure	400 PSI	400 PSI
Pump revolution	1000	1000
Power (hp)	1	2
L x w x h (in mm)	265 x 230 x 260	275 x 270 x 265
Weight (without oil & pulley)	4.7 kg (approx)	7 kg (approx)

**ASPEE GROUP OF COMPANIES**

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.  
Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: [aspee@aspee.net](mailto:aspee@aspee.net). Website: [www.aspee.com](http://www.aspee.com)

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY