

ASPEE BILI HTP POWER SPRAYER



CODE: PSB30A1N



CODE: PSB30A1NB



Suitable for large spraying operations in Orchards, Coffee, ground crops etc.

General Description:

ASPEE-BILI HTP horizontal triplex power sprayer unit, developing up to 500 psi (35 bar) pressure and giving free discharge of 30 lit/min at 900 rpm. Sprayer Supplied with pulley, pressure vessel, pressure indicator, by pass cum pressure regulator valve, 3 meter long by-pass & suction hose with strainer, couplings for delivery hose.

Special Features:

- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Heavy duty industrial quality brass stamping material
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting Rod
- Control valve assly. With pressure regulator, by-pass
- Pulsation free spray
- Develop pressure up to 500 psi max.

ASPEE BILI HTP POWER SPRAYER**CODE: PSB30A1N****CODE: PSB30A1NB**

Technical Description		
Model	PSB30A1N	PSB30A1NB
Material of Construction	C.I.	BRASS
Suction capacity (lpm)	30	
Normal working pressure	100 - 200 PSI	
Max. Pressure	500 PSI	
Pump revolution	950	
Power (hp)	3 ~ 4 HP	
L X W X H (in mm)	340 X 300 X 295	337 X 305 X 295
Weight (without oil)	7.5 kg (approx)	7.7 kg (approx)

**ASPEE GROUP OF COMPANIES**

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.
Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY