



HTP SG

CODE : PS16/SG

POWER OPERATED

**Suitable for large spraying operations in
Orchards, Coffee, Rubber Plantation & Irrigation**

Technical Description

Code	PS16/SG
Suction Capacity	36 lit/min
Normal working pressure	100-200 psi(7-14 bar)
Maximum Pressure	400 psi(28 bar)
Material of Valve Box, Delivery chamber & Suction Chamber	SG IRON
Pump revolution	950 rpm
Power requirement	3Hp
Weight (without Oil) (With accessories) (approx)	15.300 kgs. (± 0.5)

General Description

ASPEE-HTP horizontal triplex piston power sprayer unit, developing 400 PSI pressure and giving free discharge of 36 LPM at 950 RPM. SG Castings Suction Chamber, Delivery Chamber & Valve box. Supplied with pulley, SS pressure vessel, pressure gauge, by pass cum pressure regulator valve, 3 meter long bypass & suction hose with strainer.

Features

- Heavy duty & efficient Sprayer with SG casting Valve Box, Delivery chamber & Suction chamber Assembly
- Industrial grade material widely used in Agricultural Applications
- Triplex Stainless steel piston & oil bath lubrication
- More durable & reliable SG casting
- Provided With 3 discharge Outlet
- Strength and Durability at par / similar to Industrial product like manifold / valve box

ASPEE GROUP OF COMPANIES