



HTP SS
CODE : PS16/SSI

POWER OPERATED

Versatile Sprayer for Agricultural as well as Industrial Application

Technical Description

Code	PS16/SSI
Suction Capacity	36 lit/min
Normal working pressure	100-200 psi(7-14 bar)
Maximum Pressure	500 to 600 psi (35 to 42 bar)
Material of Valve Box, Delivery chamber & Suction Chamber	Stainless Steel Investment casting
Pump revolution	950 rpm
Power requirement	3Hp
Weight (without Oil) (With accessories) (approx)	15.300 kgs. (± 0.5)

Industrial Application

- Food processing Industry
- Chemical Industry
- Corrosion Resistance
- High Pressure testing
- High Pressure cleaning
- Car wash

General Description

ASPEE-HTP horizontal triplex piston power sprayer unit, developing 600 PSI pressure and giving free discharge of 36 LPM at 950 RPM. Stainless Steel Investment Castings Suction chamber, Delivery chamber, Valve box & Valve chamber. Supplied with pulley, SS Pressure vessel, pressure gauge, by pass cum pressure regulator valve, 3 meter long bypass & suction hose with strainer.

Features

- More durable & reliable S.S. Investment casting Valve Box, Delivery chamber & Suction chamber Assembly
- Abrasion resistance & heat resistance material
- Excellent resistance to petroleum based products and acidic spray solutions
- Heavy duty & efficient Sprayer with S.S. Investment casting Valve Box, Delivery chamber & Suction chamber Assembly
- Triplex Stainless steel piston & oil bath lubrication
- High wear & Corrosion Resistance S.S. Investment casting
- Provided With 3 discharge Outlet

ASPEE GROUP OF COMPANIES